# 5000 Series Tire Changers

VERSATILITY

SPEED

**Our 5000 Series Tire Changers are the workhorses of the tire service business. They're easy to use, incredibly durable, and fast.**

## 5040 A/E Rim Clamp®

The 5040A/E is a highly capable, cost effective changer designed to service a variety of applications- including most OE fitments.

- Clamps wheels externally up to 21".
- 1.5 HP air drive or 1.0 HP Electric motor.
- Pedal activated X-shaped tabletop, clamps and bead loosener.
- Perfect choice for busy shops who require flexibility and volume.

**Speed:** Self centering clamps and bead loosening system add speed through simple operation.

**Accuracy:** Precision gauges mean accurate inflation, and our X-shaped tabletop provides the right clamping pressure for even the most delicate alloy wheels without damage.

**Durability:** Super-tough fiber reinforced composite air cylinders virtually never wear out. Bead loosener has extra support blocks for extra protection and durability.

**Ease of Use:** Foot controls are positioned for easy access. Built-in bead sealing jets and table top inflation simplify job completion.

## 5065 AX/EX Rim Clamp®

The 5065 AX/EX is the industry standard for tire service because of its speed, versatility, and value. You may also add an Inflation Guard for additional operator protection.

- Exclusive pedal-actuated X-shaped tabletop provides support for the most delicate wheels.
- Handles broad range of wheels and tires, from 6" to 26" in diameter and rims up to 14" wide.
- One-control manual swing arm adjusts horizontal tool head position while easy second control adjusts vertical height.
- 1.5 HP air drive system provides plenty of power plus infinite wheel control.
- Extra storage places everything at operator's fingertips.
- The extended tabletop services a broader range of wheels.
- Bead loosener has three support blocks for extra protection and durability.
- Built in bead sealing jets and tabletop inflation for faster work.
- Easy operation allows for fast training and high productivity.

# 5000 SERIES TIRE CHANGERS

## ACCESSORIES

See accessory catalog or web for more choices.

New extended reach Robo-Arm™ retrofit can make changing low profiles and runflats fast and almost effortless. (#85009943)

Bump-N-Roll saves time and effort in bead loosening by making it easy to put heavier wheels in place. (#8183491)

Bead loosener and lift tool socks help give you total alloy wheel protection from start to finish.

X-Out-clamps externally clamp wheels from 13 to 24 inches. (#8184327)

Optional inflation guard kit helps protect operator in case of tire explosions. (#8184177)


**HENNESSY INDUSTRIES, INC.**
Manufacturer of Ammco®, Coats® and BADA® Automobile Service Equipment, Tools and Accessories.
1601 J.P. Hennessy Drive
LaVergne, TN 37086-3565
800-688-6496 or 615-641-7533
**Hennessy Canada**
2430 Lucknow Drive, Unit #9
Mississauga, Ontario L5S 1V3
905-672-9440 Printed in USA.

**www.ammcoats.com**


Part No. 941065 Rev.5 05/09


**Note: "A" designation = Air Drive "E" = Electric Drive**
**"AX" = Air Drive/Extended Tabletop.**
**"EX" = Electric Drive/Extended Tabletop.**

| FEATURES to be compared | MODELS 5065 AX & EX | 5040 A & E |
|---|---|---|
| **WHEELS HANDLED:** Alloy and steel | ● | ● |
| **MOUNT/DEMOUNT MECHANISM:** Manually swings away from wheel | ● | ● |
| **TOOL HEAD OFFSET:** Manual | ● | ● |
| **X-SHAPED TABLETOP:** For perimeter support of wheel | ● | ● |
| **EXTENDED TABLETOP:** For rims up to 22" external, 26" internal | ● | |
| **CLAMPING:** Four wheel clamps actuated by 3-3/4" fiber/composite cylinder | ● | ● |
| **BEAD LOOSENING SYSTEM:** Foot control; handles wheels 2" to 12" | | ● |
| Foot control; handles wheels 2" to 17" | ● | |
| **DRIVE SYSTEM OPTIONS:** 1.5 HP air drive | ● | ● |
| 110v single phase-60 cycle electric drive | ● | ● |
| **PRESSURE LIMITER:** Standard | ● | ● |
| **BEAD SEATING RESERVOIR:** 3.8 gal. capacity in vertical tower | ● | ● |
| **INFLATION GAUGE:** Permanent in upper tower, 0 to 60 PSI | ● | ● |
| **AIR SUPPLY GAUGE (CAL OSHA):** 0 to 300 PSI | ● | ● |
| **WATER FILTER:** Standard | ● | ● |
| **STORAGE TRAY:** Standard | ● | |
| Optional | | ● |
| **INFLATION GUARD SYSTEM:** Standard | | |
| Optional | ● | ● |

## SPECIFICATIONS

| | 5065 AX & EX | 5040 A & E |
|---|---|---|
| Rim Diameter | 6"-22" External; 8"-26" Internal | 10"-21" External; 12"-24" Internal |
| Rim Width | 14" Max | 10-1/2" Max |
| Tire Diameter | 50" Max | 50" Max |
| Drive System | Air and Electric | Air and Electric |
| Air Source | 110 to 175 PSI 14 to 15 SCFM @ 150 PSI | 110 to 175 PSI 14 to 15 SCFM @ 150 PSI |
| Chassis Footprint | 35"w x 44"d x 75"h | 35"w x 44"d x 70"h |
| Shipping Weight | 585 lbs. | 585 lbs. |

Specifications subject to change without notice. Units may not be exactly as pictured.